LONGSHINE™
Your vision. Our passion.

15" POS ALL-IN-ONE TERMINAL

Powerful . Fanless . Ultra Slim

Features:

LONGSHINE's fanless 15S-BW was designed for applications which require high performance and installation feasibilities. Through it's high degree of adjustable operation angles, it adapts to maximal installation environments. Your total cost of ownership will also be significantly reduced through competitive hardware costs, improved efficiencies and minimal administration efforts. Finally, high product quality ensures a long lifecycle.

Maximise the usage, minimize the cost

Platforms Braswell covers all needs

■ Flexibility of power

Touch type

■ 15" Projected Capacitive Touch

Zero bezel design

■ Water and dust proof sealing from the front for wide range of usage

New feasible compact design

■ Easily configured on the counter to suit the needs and demands of the user

Fanfree design

■ Contributes to a pleasant quiet working environment

Performance

Fits into any POS software environment with relative ease

■ 15S-BW provides a wide range of platforms to cover all software needs

intel inside™ CELERON® intel inside™ PENTIUM® RoHS Compliant CE FC

Hardware Specification	
CPU	Intel® Celeron® N3160 or Pentium N3710 SoC
System Memory	DDR3L 1600 2GB Standard, Maximum 8G
Graphics	Intel® HD Graphics Gen8 LP 16EUs
Audio	RealTEK HD Audio Codec
Display	15" TFT-LCD /1024 X 768 (LED backlight)
	Touch Screen:15" Projected Capacitive touch
Storage	1x 2.5" SATA III 64G SSD
External I/O Ports	
USB	5 (2 x USB 3.0 , 3 x USB 2.0)
COM port	3 x RJ45 with 5V/12V power selectable
uUSB	1
LAN	1 x 10/100/1000Mbps
DC input	1 x 12V
HDMI	1 x Type-C
SPDIF	1
GPIO	1
Audio I/O	1 x Combo Jack
Cash drawer	1 x RJ-11 (12V/24V)
DC output	1 x 12V DC out (optional)
Optional Peripherals	
MSR	3 Tracks , JIS-I or II
2-in-1 Reader	MSR+ RFID or MSR+iButton
Customer Display	2 x 20 VFD stand-alone type
2nd Display	7"/10"/15" monitor
Wireless LAN	802.11 b/g/n, Blue Tooth 4.0 SiP wireless module
Speaker	2 x 3W
SD Slot	1
OS Support	
Windows	Windows Embedded POSReady 7 (64bit) , Windows Embedded Industry 8.1 (64bit) , Win10 IoT Enterprise for Retail (64bit)
Linux	Per Request

Features and specifications are subject to change without prior notice.