

Symphone N2S

Android Smartphone PDA



Features

- ◆ **Powered by a Newland scanning module.**

The N2S is armed with a high performance 1D/2D scanning module, ideal for day in and day out heavy scanning.

- ◆ **First time everytime barcode scanning.**

The N2S has a 25 degree scan angle, making scanning easy and comfortable while reading the screen.

- ◆ **Built to withstand heavy use.**

A durable design, reinforced by carefully selected materials, guarantees low maintenance costs even for use in harsh conditions.

- ◆ **High quality PCAP Touch.**

The N2S supports both dry and moist hands, as well as gloved fingertip touch input. Ideal for use in severe conditions, such as rain, snow and dust.

- ◆ **Supplied with Symphone N2S charging stand.**



Application Scenarios

Warehouse management, Inventory counting, manufacturing, access control, back office inventory management, stock management, food traceability.

Symphone N2S

Android Smartphone PDA

Specifications	Dimensions	169*72*23.8mm	
	Keys	Front: Number keys, Five-navigation key, Back key, Del key Enter/End key, Dial key, Self-definition (F1, F2, F3) keys Sides: Power key, Left-scan key, Right-scan key, Function key	
	Input	English, pinyin, handwriting, soft-keyboard	
Product	OS	Android 5.1	
Performance	CPU	Dual-core 1.2 GHz	
	Screen	IPS, 3.5 inch WVGA, 480*800 pixel	
	Touch	Multi-point PCAP (Projective Capacitive Touch)	
	Memory	ROM	4GB
		RAM	1GB
Barcode Scanning	1D	Code39, Codabar, Code128, Interleaved 2 of 5, UPC, EAN, MSI and more	
	2D (optional)	QR, PDF417, DataMatrix, MaxiCode and more	
Network	Wi-Fi	IEEE 802.11 b/g/n	
	WCDMA/GSM	WCDMA: 2100 MHz	
		GSM: 900 MHz, 1800 MHz	
	Bluetooth	BT 3.0 + HS, BT v2.1 + EDR	
	Camera	High-definition, auto focus	
	GPS	GPS, AGPS	
Battery	Capacity	4000mAh	
Endurance	Standby	500 hours	
	Talking	20 hours	
Ports & Accessories	T-Flash	Micro SD/TF (up to 32 GB)	
	SIM	Mini-SIM card	
	Jack	Micro USB, 3.5mm Audio jack, DC jack	
	Charging stand (included)	Charges device and battery at the same time	
	Others	Printer (optional) supports BT-connected devices, Adapter, Cable, Belt	
Certificates & Protection	Industrial protection	IP64	
	Drop	1.5 meter drop to concrete	
	Certificates	CTA, CCC, CE, RoHS	
	Laser Safety	IEC2 / FDA II, IEC60825 / EN60825-1	

Specifications are subject to change without notice.

Version: V1.0

Newland EMEA HQ
+31 (0) 345 87 00 33
info@newland-id.com

Newland D-A-CH
+49 (0) 6182 82916-16
info@newland-id.de

Newland France
+31 (0) 345 87 00 33
france@newland-id.com

Newland Benelux
+31 (0) 345 87 00 33
benelux@newland-id.com

Newland Ibérica
+34 (0) 93 303 74 66
info@newland-id.es

Newland Italy
+39 (0) 342 056 2227
italy@newland-id.com

Newland Nordic & Baltic
+46 (0) 708 847 767
nordic@newland-id.com

Newland UK
+44 (0) 1442 212 020
sales@newland-id.co.uk

Newland Russia
+31 (0) 345 87 00 33
russia@newland-id.com

Newland South Africa
+27 (0) 11 553 8010
info@newland-id.co.za

Newland Middle East
+31 (0) 345 87 00 33
middleeast@newland-id.com

Newland Turkey & Iran
+90 (0) 544 538 40 49
turkey@newland-id.com
iran@newland-id.com