



Enhanced performance Impact Receipt Printer

SRP-275II

BIXOLON SRP-275II is more powerful and enhanced performance impact receipt printer to address customers' needs in restaurant, hospitality and retail industries.

The fastest speed in its class(5.1 lps) allows kitchen orders to print faster than ever with two color, black and red printing to highlight special offers and print logos. Compact size with embedded power supply maximizes the efficiency of working environment.

Eco-friendly design of the lowest standby power and various international standards provide reliability of the SRP-275II to the users.

HIGHLIGHTS

- Fastest Print Speed up to 5.1 lps
- Eco-friendly design
 - Lowest Standby Power (0.91w)
- Compact Design
 - Embedded Power Supply
- Black Mark Sensor
- Fast USB Interface
 - USB 2.0 HS
- Large Capacity of Data Buffer
 - 64KB Data Buffer
 - 256KB NV Image

APPLICATIONS

- Retail
- Hospitality
- Healthcare
- Banking
- Parking

OTHER VALUE-ADDED FEATURES

- Two color printing
- Easy to operate
 - Easy paper loading
 - Easy to install ribbon cartridge
- Proven reliability
 - 18,000,000 MCBF
 - 1,500,000 auto-cuts
- Bi-directional print
- User friendly software tool
 - Logo download(NV image tool)
 - Code page selection(Virtual Memory Switch Manager)
 - Firmware download
- Two different type
 - SRP-275IIA(without Auto-cutter)
 - SRP-275IIC(with Auto-cutter)
- Many valuable options
 - Splash Proof Cover(RSC - 275)
 - External Buzzer(RBC-100)
 - BIXOLON Melodist(RMB-100)
- Various International Standards

BIXOLON SRP-275II SPECIFICATIONS

PRINT	PRINTING METHOD	9 Pin Serial Dot Matrix
	PRINTING SPEED	Max 5.1 lps
	PRINTING WIDTH	63.5mm(2.5 inch)
	RESOLUTION	Horizontal: 80dpi Vertical: 144dpi
	CHARACTER SIZE	Font A: 9 x 9, Font B: 7 x 9, Korean: 17 x 9, Chinese: 16 x 16
	CHARACTERS PER LINE	Font A: 35 (3half dot: 33) , Font B: 40, Korean: 20, Chinese: 22 (3half dot: 21)
	CHARACTER SET	Alphanumeric Character: 95 Extended Graphics Pages: STD - 128 x 27, CHN - 128 x 21, KOR - 128 x 1 International Character: 48
	Sensor	Paper End, Black-mark, Paper Near End, Wall Mounting Paper Near End(option), Rear Cover Open
	Printing Direction	Bi-direction
	Receive Buffer	64Kbyte
	NV Image	256Kbyte
	CUTTER TYPE	A: Tear-bar C: Auto Cutter (Rotary)
PAPER	WIDTH	76.0 Ø 0.5mm
	MAX. ROLL DIAMETER	83mm
	SUPPLY METHOD	Easy Paper Loading
RELIABILITY	PRINTER UNIT (MCBF)	18,000,000 lines
	HEAD	300,000,000 dots/wire
	AUTO CUTTER	1,500,000 cuts
INK RIBBON	COLOR	Black & Red
	RELIABILITY (CHARACTERS)	Black : 1,500,000 Red : 750,000
INTERFACE	Serial(RS-232C), Parallel(IEEE 1284), Ethernet, USB 2.0 HS	
DRIVER	Windows, OPOS, Linux, Virtual COM, Mac	
EMULATION	ESC/POSTM	
POWER SUPPLY	AC 100 ~ 240V / DC 24V, 1.5A	
DIMENSIONS (WXLXH)	160 x 239 x 157mm	
WEIGHT (STANDARD I/F, NOT PAPER)	A: 2400g	
	C: 2500g	
INTERNATIONAL	FCC, UL, CE, CB, GS, GOST-R, CCC, KCC	
STANDARDS	0 ~ 40°C (32 ~ 104°F)	
OPERATING TEMPERATURE	Wall Mount Bracket(RWM - 350), Splash Proof Cover(RSC - 275), External Buzzer(RBC-100), BIXOLON	
OPTION	Melodist(RMB-100), Ribbon Cartridge(RRC-201BR: Black/Red, RRC-201B: Black)	

BIXOLON Headquarters

Address 7~8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, KOREA
Tel +82 (0) 31 218 5500 Fax +82 (0) 31 218 5589
E-mail sales@bixolon.com

BIXOLON America Inc.

Address 3171 Fujita St Torrance,
CA 90505
Tel +1 858 764 4580 Fax +1 310 257 6869
E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Address Tiefenbroicher Weg 35,
40472 Düsseldorf
Tel +49 211 68 78 54 0 Fax +49 211 68 78 54 20
E-mail sales@bixolon.de