

# HR1550-35 Wahoo

## Handheld Barcode Scanner



### Features

#### ◆ Data acquisition.

The HR1550-35 Wahoo 1D handheld barcode scanner is the corded model of HR15 series and comes with a coiled cable. It can easily read most of the 1D barcodes.

#### ◆ Multiple interfaces.

The HR1550 Wahoo supports standard RS-232 / USB / PS2 PC interfaces.

#### ◆ Lightweight ergonomic design.

The housing of HR1550 Wahoo is made in a way to comfortably fit in your hand, so you can operate all day long. It reduces fatigue and enhances your productivity.

#### ◆ Durable construction.

The HR1550 Wahoo was created with use in harsh and demanding environments in mind. With a sealing of IP54, the device is protected against dust and moisture and with a drop resistance of 1.5m it can withstand everyday drops and bumps.

#### ◆ HR15 handheld scanner stand available

The smart foldable stand for the HR1550-35 can be ordered as an accessory. For the model HR1550-35F, the stand is included in a SET.



### Application Scenarios

With good performance, this rugged and compact scanner is suitable for applications in supermarkets, shopping malls, warehouse environment application and more.

# HR1550-35 Wahoo

## Handheld Barcode Scanner

Performance	Light Source	620nm visible red LED
	Scan Pattern	CCD linear image
	Symbologies	Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code 93, UCC/ EAN-128, GS1 Databar, PDF417, MicroPDF417, etc.
	Resolution	≥ 4mil
	Scan Angle	42°
	Reading Angle	42°
	Scan Rate	300 scans per second
	Minimum Symbol Contrast	25%
	Reminder	Beep and LED indicator
	Interface	RS-232, USB 1.1, PS2
Mechanical/	Dimensions	113.5 x 73 x 159 mm
Electrical	Weight	152g
	Power Adaptor	Output: DC5V, ≥1.5A, Input: AC 100~240V, 50~60Hz
Environmental	Operating Temperature	-10°C to 50°C (14°F to 122°F)
	Storage Temperature	-20°C to 60°C (-4°F to 140°F)
	Humidity	0 to 95% (non-condensing)
	Drop	1.5m drop to concrete
Accessories	Cable	Coiled cable included
	Stand	The smart foldable stand can be ordered as an accessory For the model HR1550-35F, the stand is included in a SET
Certifications		FCC Part15 Class B, CE EMC Class B, CCC

\*Specifications are subject to change without notice.\*

**Newland EMEA HQ**  
+31 (0) 345 87 00 33  
info@newland-id.com

**Newland D-A-CH**  
+49 (0) 6182 82916-16  
info@newland-id.de

**Newland France**  
+31 (0) 345 87 00 33  
france@newland-id.com

**Newland Benelux**  
+31 (0) 345 87 00 33  
benelux@newland-id.com

**Newland Ibérica**  
+34 (0) 93 303 74 66  
info@newland-id.es

**Newland Italy**  
+39 (0) 342 056 2227  
italy@newland-id.com

**Newland Nordic & Baltic**  
+46 (0) 708 847 767  
nordic@newland-id.com

**Newland UK**  
+44 (0) 1442 212 020  
sales@newland-id.co.uk

**Newland Russia**  
+31 (0) 345 87 00 33  
russia@newland-id.com

**Newland South Africa**  
+27 (0) 11 553 8010  
info@newland-id.co.za

**Newland Middle East**  
+31 (0) 345 87 00 33  
middleeast@newland-id.com

**Newland Turkey & Iran**  
+90 (0) 544 538 40 49  
turkey@newland-id.com  
iran@newland-id.com