

Data Sheet

15" All-in-One POS Terminal

Performance . Easy maintenance . Stability

LONGSHINE's new RDT-150 was designed for heavy-duty tasks in environments such as restaurants, hotels and shops.

15" TFT LCD display with touch panel in wide tilting angle offers the user maximal flexibility and convenience.

Your total cost of ownership will also be significantly reduced through competitive hardware costs, improved efficiencies and minimal administration efforts. Finally, high product quality ensures a long life cycle.



Performance

Platforms from Intel Celeron for performance.

- Fits into any POS software environment with relative ease
- RDT-150 provides performance to cover POS software needs

Maximize the usage, minimize the cost

Removable base for panel mount application

- Flexibility of usage

Cost effective

Excellent cost-performance ratio

- Developed for the highest CP value

Compact design

Tidy desk with more space left

- Small footprint for limited counter space

Water proof


- Water spill resist around the bezel

System compatibility


- Runs on Windows OS or Linux



I/O Interface



Dimensions



Technical Specifications

Model	RDT150FB-AV
Processor	INTEL® Celeron Processor J1900 (Clock speed: 2.0 GHz; Turbo Speed: 2.4 GHz; Quad Core)
Graphics	Intel® Gen7 Graphics DX 11, OGL 3.2
Storage Device	204-pin DDR3L SO-DIMM Socket x 2 Support up to 8GB of system memory
Touch LCD Display	
Display	<ul style="list-style-type: none"> 15" TFT LCD with native resolution 1024 x 768 5-wired Resistive Touch
External IO Ports	
Serial Port	4 x DB-9 with 5V/12V power selectable, COM1 (RS232/RS422/RS485)
USB Port	USB 2.0 x 6
Cash Drawer Port	1 x RJ-11 (12V/24V) 12/24V power output by jumper adjustable
VGA	1
LAN Port	1 x 10/100/1000 Mbps
Printer Port	1
Audio	2; MIC and Line-out
Expansion Slot	
PCI-E Slot	1
Mini PCIe socket	2, (1 shared with mSATA)
Optional Peripherals	
Magnetic Stripe Reader	3-Track, JIS-I or II
Customer Display	2 x 20 VFD
2nd Display	7" / 10" external USB I/F
2-in-1 Reader	MSR + i-Button

OS Support	
Windows	POSReady 7, Win 7, Win 8, Embedded 8.1 Industry
Linux	Per Request
Environment	
Green Product	RoHs, REACH
EMI/Safety	CE, FCC Class A
Operating Temperature	0° to 40° (32° F ~ 104° F)
Storage Temperature	-10° to 55° (14° F ~ 131° F)
Relative Humidity	10% ~ 90% (Non-Condensing)

Dimension	
Dimension	380(W) x 217(D) x 306(H) mm
Weight	5. kg
Others	
Indicator	Power, HDD on LED
Button	Power on/off, Reset, UP/Down
Buzzer	Yes

Features and specifications are subject to change without prior notice.

More information

Longshine Services

In addition to models from Longshine RDT-150, Longshine provides a wide range of platform solutions. Combine reliable Longshine products with the best services, know-how and worldwide partnerships.

Longshine Hardware Portfolio

Longshine offers a full portfolio of IT hardware ranging from networking, POS, digital signage and e-books. This allows customers to single source from one vendor to ensure installation compatibility and reduce response times for technical enquiries, and changing business requirements.

POS Products

<http://pos.longshine.de>
info@longshine.de

Networking Products

<http://network.longshine.de>
info@longshine.de

E-Book

tolino@longshine.de

Digital Signage Products

info@longshine.de

ODM/OEM of specialized IT products

info@longshine.de

More information

To learn more about Longshine RDT-150, please contact your Longshine sales representative or Longshine Business partners, or visit our website.
www.longshine.de

LONGSHINE VISION

It's our policy to be open minded and mechanical flexible to support our Business partners, and to also secure projects from different technical enquiries/opportunities. By listening and understanding to market needs, we also aim to contribute technical knowledge to continuously improve and create standard models with high CP values. To become a Longshine Business partner, please contact via
info@longshine.de



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. All liability that the data and illustrations are complete, actual or correct is excluded. Copyright © 1981-2015 LONGSHINE Technologie GmbH.

Disclaimer

Part number RDT150FB-AV. Model name RDT-150 and the Stylized LONGSHINE Logo are trademarks or registered trademarks of LONGSHINE Technologie GmbH. Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. All other trademarks are property of their respective owners.

Contact

LONGSHINE Technologie GmbH
 Headquarters:
 An der Strusbek 9, 22926 Ahrensburg, Germany
 TEL: +49 4102 49220 FAX: +49 4102 40109

www.longshine.de
info@longshine.de

Part number RDT150FB-AV, model name RDT-150 and the Stylized LONGSHINE Logo are trademarks or registered trademarks of LONGSHINE Technologie GmbH. All other trademarks are the property of their respective owners.

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. All liability that the data and illustrations are complete, actual or correct is excluded. Copyright © 1981-2016 LONGSHINE Technologie GmbH.